

Industry standard for Hasteco Heat Transfer System-Tubular heater

Sheath length	φ 6.0mm	φ 6.6mm	φ 8mm	φ 8.5mm	5*5mm	6*6mm	8*8mm
	Standard wattage(w), 230v,cold length 30-35mm						
300	450	500	600	650	400	500	650
325	500	550	650	700	450	550	750
350	550	600	700	750	500	600	800
375	550	600	750	800	550	650	850
400	600	650	800	850	550	650	900
425	650	700	850	900	600	700	950
450	700	750	900	950	650	750	1000
475	700	800	950	1000	650	800	1050
500	750	850	1000	1050	700	850	1100
525	800	850	1050	1100	750	900	1200
550	850	900	1100	1150	750	900	1250
575	850	950	1150	1250	800	950	1300
600	900	1000	1200	1300	850	1000	1350
625	950	1050	1250	1350	900	1050	1400
650	1000	1100	1300	1400	900	1100	1450
675	1000	1100	1350	1450	950	1150	1500
700	1050	1150	1400	1500	1000	1200	1550
725	1100	1200	1450	1550	1000	1200	1600
750	1150	1250	1500	1600	1050	1250	1700
775	1150	1300	1550	1650	1100	1300	1750
800	1200	1350	1600	1700	1100	1350	1800
825	1250	1350	1650	1750	1150	1400	1850
850	1300	1400	1700	1800	1200	1450	1900
875	1300	1450	1760	1850	1250	1450	1950
900	1350	1500	1800	1900	1250	1500	2000
925	1400	1550	1850	1950	1300	1550	2050
950	1450	1600	1900	2050	1350	1600	2150
975	1450	1600	1950	2100	1350	1650	2200
1000	1500	1650	2000	2150	1400	1700	2250
1025	1550	1700	2050	2200	1450	1700	2300
1050	1600	1750	2100	2250	1450	1750	2350
1075	1600	1800	2150	2300	1500	1800	2400
1100	1650	1800	2200	2350	1550	1850	2450
1125	1700	1850	2250	2400	1600	1900	2500
1150	1750	1900	2300	2450	1600	1950	2600
1175	1750	1950	2350	2500	1650	1950	2650
1200	1800	2000	2400	2550	1700	2000	2700
1225	1850	2050	2450	2600	1700	2050	2750
1250	1900	2050	2500	2650	1750	2100	2800
1275	1900	2100	2550	2700	1800	2150	2850
1300	1950	2150	2600	2800	1800	2200	2900
1325	2000	2200	2650	2850	1850	2250	2950
1350	2050	2250	2700	2900	1900	2250	3000
1375	2050	2300	2750	2950	1950	2300	3100
1400	2100	2300	2800	3000	1950	2350	3150
1425	2150	2350	2850	3050	2000	2400	3200
1450	2200	2400	2900	3100	2050	2450	3250
1475	2200	2450	2950	3150	2050	2500	3300
1500	2250	2500	3000	3200	2100	2500	3350